



Printing date 30.08.2013 Revision: 30.08.2013

1 Identification of the substance/preparation and of the company/undertaking

· Product details

Product name: Muc-Off Chain Cleaner 400ml

· Article number: 950

· Application of the substance / the preparation Cleaner solvent

Manufacturer/Supplier:

Muc-Off Ltd

1st Floor, Unit 1, Concept Office Park,

Innovation Close, Poole, Dorset,

BH12 4QT, UK

Tel: +44 (0)1202 307790

- · Further information obtainable from: ag@muc-off.com
- Information in case of emergency:

During normal opening times 8.30am - 5.30pm Monday to Friday:

Tel: +44 (0)1202 307790

2 Hazards identification

· Hazard description:



F+ Extremely flammable

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurized container.

R 12 Extremely flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

· Chemical characterization

Description: Active substance with propellant

CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy	Xn; R 65-66	50-100%
CAS: 106-97-8 EINECS: 203-448-7	butane	F+; R 12	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane	F+; R 12	2.5-10%
CAS: 68155-06-6	Fatty Acid Amide	Xi; R 38-41	1.0-2.5%
CAS: 68439-50-9	Fatty alcohol C12-C14 with approx. 2 moles EO	Xi, N; R 41-50	0.1-1.0%

 Ingredients accordi 	ng to detergents	guidline 648/2004/EC
---	------------------	----------------------

aliphatic hydrocarbons

≥ 30%

Printing date 30.08.2013 Revision: 30.08.2013

Product name: Muc-Off Chain Cleaner 400ml

(Contd. of page 1)

non-ionic surfactants

< 5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

· Suitable extinguishing agents:

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: Mount respiratory protective device.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: No special measures required.
- · Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility:

Observe official regulations on storing packagings with pressurized containers.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 3)

Printing date 30.08.2013 Revision 30.08.2013

Product name: Muc-Off Chain Cleaner 400ml

(Contd. of page 2)

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL | Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m3, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

OEL | Short-term value: 3600 mg/m³, 2000 ppm Long-term value: 1800 mg/m3, 1000 ppm

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Filter AX/P2

Protection of hands:



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

General Information	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. -44°C
Flash point:	-97°C
Ignition temperature:	240.0°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.

(Contd. on page 4)

Printing date 30.08.2013 Revision: 30.08.2013

Product name: Muc-Off Chain Cleaner 400ml

(Contd. of page 3) · Explosion limits: 0.6 Vol % Lower: Upper: 8.5 Vol % · Vapour pressure at 20°C: 2100.0 hPa · Density at 20°C: 0.70800 g/cm3 · Solubility in / Miscibility with Not miscible or difficult to mix. water: · Solvent content:

10 Stability and reactivity

Organic solvents:

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

95.7 %

11 Toxicological information

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

13 Disposal considerations

- · Product:
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID (cross-border)
- 2 5F Gases. · ADR/RID class:
- · Danger code (Kemler): 23
- 1950 · UN-Number:
- · Packaging group:
- · Hazard label
- Description of goods: 1950 AEROSOLS
- · Limited quantities (LQ) LQ2
- · Maritime transport IMDG:
- · IMDG Class: 2.1
- 1950 · UN Number:

(Contd. on page 5)

Printing date 30.08.2013 Revision: 30.08.2013

Product name: Muc-Off Chain Cleaner 400ml

(Contd. of page 4)

· Label 2.1 · Packaging group: -

• EMS Number: F-D,S-U
• Marine pollutant: No
• Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:

· ICAO/IATA Class: 2.1 · UN/ID Number: 1950 · Label 2.1

Packaging group: Proper shipping name: AEROSOLS, flammable

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



F+ Extremely flammable

· Risk phrases:

- 12 Extremely flammable.
- 66 Repeated exposure may cause skin dryness or cracking.

· Safety phrases:

- 2 Keep out of the reach of children.
- 23 Do not breathe fumes/aerosol.
- 24 Avoid contact with skin.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

· National regulations:

· Technical instructions (air):

	Class	Share in %
	NK	50-100

- · VOC-CH 95.70 %
- · VOC-EU 677.6 g/l
- Danish MAL Code 5-3

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 12 Extremely flammable.
- 38 Irritating to skin.

(Contd. on page 6)

Page 6/6

Health & Safety Sheet According to 1907/2006 EEC (REACH), Article 31

Printing date 30.08.2013 Revision 30.08.2013

Product name: Muc-Off Chain Cleaner 400ml

(Contd. of page 5)

- 41 Risk of serious damage to eyes.
- 50 Very toxic to aquatic organisms.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- · Department issuing MSDS: Research & Development
- · Contact: Adam Goudge

...